

Automation Technology > Automation Systems > Industrial Automation Systems SIMATIC
> PLC > Modular Controller SIMATIC S7 > S7-1200 > Communication

6ES7241-1AH30-0XB0 COMMUNICATION MODULE CM 1241, RS232

Technical / CAx data

Technical Data CAx data

**SIMATIC S7-1200, COMMUNICATION COMMUNICATION MODULE CM 1241,
RS232, 9 PIN SUB D (FEMALE), SUPPORTS MESSAGE BASED FREEPORT**

Current consumption

Current consumption, max.	220 mA; from L5+; logic
----------------------------------	-------------------------

Power losses

Power loss, typ.	1.1 W
-------------------------	-------

Interfaces

Number of interfaces	1
-----------------------------	---

Interface physics, RS 232C (V.24)	Yes
--	-----

Point-to-point

Cable length, max.	10 m
---------------------------	------

Integrated protocol driver

ASCII	Yes
--------------	-----

Climatic and mechanical conditions for storage
and transport

Climatic conditions for storage and transport

Free fall

Drop height, max. (in packaging)	0.3 m
---	-------

Temperature

Permissible temperature range	-40 °C to +70 °C
--------------------------------------	------------------

Air pressure acc. to IEC 60068-2-13

Permissible air pressure	1080 to 660 hPa
---------------------------------	-----------------

Relative humidity

Permissible range (without condensation) at 25 °C	95%
--	-----

Mechanical and climatic conditions during
operation

Climatic conditions in operation

Air pressure acc. to IEC 60068-2-13

Permissible air pressure	1080 to 795 hPa
---------------------------------	-----------------

Software

Runtime software

Target system	Yes
----------------------	-----

Dimensions and weight

Dimensions

Width	30 mm
--------------	-------

Height	100 mm
---------------	--------

Depth	75 mm
--------------	-------

Weight

Weight, approx.	150 g
------------------------	-------

Status

Jan 17, 2011

© Siemens AG 2011 - Corporate Information - Privacy Policy - Terms of Use