

Rittal – The System.

Faster – better – worldwide.

➤ Rittal – North American Industrial Buyer's Guide



ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES



FRIEDHELM LOH GROUP

WM Wallmount

Depth: 8" (210 mm), Height: 20 - 30" (500 - 760 mm)

Height (H1) inches (mm)	PU	20 (500)	20 (500)	24 (600)	24 (600)	24 (600)	30 (760)	Page
Width (B1) inches (mm)		16 (400)	20 (500)	16 (400)	20 (500)	24 (600)	24 (600)	
Depth (T1) inches (mm)		8 (210)	8 (210)	8 (210)	8 (210)	8 (210)	8 (210)	
Panel Height (G1) inches (mm)		19 (475)	19 (470)	22 (570)	22 (570)	22 (570)	29 (730)	
Panel Width (F1) inches (mm)		14 (354)	18 (449)	14 (354)	18 (449)	22 (549)	22 (549)	
Part No.	1	WM201608N4	WM202008N4	WM241608N4	WM242008N4	WM242408N4	WM302408N4	
Door(s)		1	1	1	1	1	1	
Weight lb (kg)		34 (15)	41 (18)	39 (18)	46 (21)	57 (26)	70 (32)	

Accessories

Handle	1	WMQTPLS6						304
Wallmount bracket for Type 304	4	2433.000						339
Dead front kit	1	DFK2016C	DFK2020C	DFK2416C	DFK2420C	DFK2424C	DFK3024C	321

Note: To order WM wallmount enclosures in stainless steel type 316L replace N4 ending with N6 (extended delivery times).

Depth: 8 - 10" (210 - 250 mm), Height: 24 - 36" (600 - 900 mm)

Height (H1) inches (mm)	PU	30 (760)	36 (900)	36 (900)	24 (600)	30 (760)	30 (760)	Page
Width (B1) inches (mm)		30 (760)	24 (600)	30 (760)	20 (500)	24 (600)	30 (760)	
Depth (T1) inches (mm)		8 (210)	8 (210)	8 (210)	10 (250)	10 (250)	10 (250)	
Panel Height (G1) inches (mm)		29 (730)	34 (870)	34 (870)	22 (570)	29 (730)	29 (730)	
Panel Width (F1) inches (mm)		28 (704)	22 (549)	28 (704)	18 (449)	22 (549)	28 (704)	
Part No.	1	WM303008N4	WM362408N4	WM363008N4	WM242010N4	WM302410N4	WM303010N4	
Door(s)		1	1	1	1	1	1	
Weight lb (kg)		86 (39)	91 (41)	111 (50)	49 (22)	154 (70)	89 (40)	

Accessories

Handle	1	WMQTPLS6						304
Wallmount bracket for Type 304	4	2433.000						339
Dead front kit	1	DFK3030C	DFK3624C	DFK3630C	DFK2420C	DFK3024C	DFK3030C	321

Note: To order WM wallmount enclosures in stainless steel type 316L replace N4 ending with N6 (extended delivery times).

Depth: 10 - 12" (250 - 300 mm), Height: 24 - 48" (600 - 1200 mm)

Height (H1) inches (mm)	PU	36 (900)	48 (1200)	24 (600)	30 (760)	36 (900)	36 (900)	Page
Width (B1) inches (mm)		30 (760)	36 (900)	24 (600)	24 (600)	30 (760)	36 (900)	
Depth (T1) inches (mm)		10 (250)	10 (250)	12 (300)	12 (300)	12 (300)	12 (300)	
Panel Height (G1) inches (mm)		34 (870)	45 (1155)	23 (570)	29 (730)	34 (870)	34 (870)	
Panel Width (F1) inches (mm)		28 (704)	33 (840)	22 (549)	22 (549)	28 (704)	33 (840)	
Part No.	1	WM363010N4	WM483610N4	WM242412N4	WM302412N4	WM363012N4	WM363612N4	
Door(s)		1	1	1	1	1	1	
Weight lb (kg)		116 (53)	178 (81)	63 (28)	77 (35)	122 (55)	146 (66)	

Accessories

Handle	1	WMQTPLS6	WMLHKLS6	WMQTPLS6				304
Wallmount bracket for Type 304	4	2433.000						339
Wallmount bracket for Type 316L	4	2433.500						339
Dead Front Kit	1	DFK3630C	DFK4836C	DFK2424C	DFK3024C	DFK3630C	DFK3636C	321

Note: To order WM wallmount enclosures in stainless steel type 316L replace N4 ending with N6 (extended delivery times).