

Antenna - RAD-ISM-2400-ANT-OMNI-6-0 - 2885919

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)


Omnidirectional antenna, 2.4 GHz, 6 dBi, linear vertical, N (female), IP55, 50 Ohm impedance



Why buy this product

- For mobile applications with a longer range

Key commercial data

Packing unit	0
Minimum order quantity	1
Catalog page	Page 650 (IF-2011)
GTIN	 4 046356 146319
Custom tariff number	85177019
Country of origin	ITALY

Technical data

General data

Frequency range	2.4 GHz
Frequency range	2.4 GHz ... 2.5 GHz
Horizontal beamwidth	360 °
Vertical beamwidth	30 °
Impedance	50 Ω
Gain	6 dBi
Connection method	N (female)
Degree of protection	IP55
Ambient temperature (operation)	-40 °C ... 75 °C
Ambient temperature (storage/transport)	-40 °C ... 75 °C
Width	22 mm
Height	250 mm

Classifications

ETIM

ETIM 2.0	EC000416
----------	----------

Antenna - RAD-ISM-2400-ANT-OMNI-6-0 - 2885919

Classifications

ETIM

ETIM 3.0	EC001698
ETIM 4.0	EC001698
ETIM 5.0	EC000416

UNSPSC

UNSPSC 11	43171611
UNSPSC 12.01	43221706
UNSPSC 13.2	43221706
UNSPSC 6.01	43171611
UNSPSC 7.0901	43221706

eCl@ss

eCl@ss 4.0	27250312
eCl@ss 4.1	27250312
eCl@ss 5.0	19070102
eCl@ss 5.1	19070102
eCl@ss 6.0	19070102
eCl@ss 7.0	19070102