

## Fuse plug - ST-SILED 24-UK 4 - 0921037

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)



Fuse plug, Nominal current: 6.3 A, Length: 33.1 mm, Width: 6.1 mm, Height: 26.5 mm, Color: black

The illustration shows the version without LED/light indicator

### Key commercial data

|                        |   |
|------------------------|---|
| Packing unit           | 1 PCE   |
| Minimum order quantity | 50 PCE  |
| Catalog page           | Page 452 (CL1-2011)   |
| GTIN                   | <br>4 017918 010294 |
| Custom tariff number   | 85363010  |
| Country of origin      | POLAND  |

### Technical data

#### General

|   |  |
|---|--|
| Note                                    | If the fuse is defective, the downstream circuit is not off load |
| Color                                   | black  |
| Insulating material                     | PA   |
| Inflammability class according to UL 94 | V2   |

#### Dimensions

|                  |         |
|------------------|---------|
| Width            | 6.1 mm  |
| Length           | 33.1 mm |
| Height NS 35/7,5 | 26.5 mm |

#### Technical data

|                           |         |
|---------------------------|---------|
| Insulating material group | CTI 600 |
| Nominal current $I_N$     | 6.3 A   |
| Nominal voltage $U_N$     | 250 V   |

# Fuse plug - ST-SILED 24-UK 4 - 0921037

## Classifications

### ETIM

|          |          |
|----------|----------|
| ETIM 2.0 | EC000897 |
| ETIM 3.0 | EC000897 |
| ETIM 4.0 | EC002018 |
| ETIM 5.0 | EC002018 |

### UNSPSC

|               |          |
|---------------|----------|
| UNSPSC 11     | 39121409 |
| UNSPSC 12.01  | 39121409 |
| UNSPSC 13.2   | 39121409 |
| UNSPSC 6.01   | 30211811 |
| UNSPSC 7.0901 | 39121409 |

### eCl@ss

|            |          |
|------------|----------|
| eCl@ss 4.0 | 27141199 |
| eCl@ss 4.1 | 27141199 |
| eCl@ss 5.0 | 27141145 |
| eCl@ss 5.1 | 27141145 |
| eCl@ss 6.0 | 27141149 |
| eCl@ss 7.0 | 27141149 |

## Approvals

### Approvals

---

#### Approvals

CSA / UL Recognized / cUL Recognized / GOST / GOST / cULus Recognized

---

#### Ex Approvals

---

#### Approvals submitted

---

#### Approval details

# Fuse plug - ST-SILED 24-UK 4 - 0921037

## Approvals

|                    |       |
|--------------------|-------|
| CSA                |       |
| Nominal current IN | 10 A  |
| Nominal voltage UN | 300 V |

|                    |       |
|--------------------|-------|
| UL Recognized      |       |
| Nominal current IN | 6.3 A |
| Nominal voltage UN | 300 V |

|                    |       |
|--------------------|-------|
| cUL Recognized     |       |
| Nominal current IN | 6.3 A |
| Nominal voltage UN | 300 V |

|      |  |
|------|--|
| GOST |  |
|------|--|

|      |  |
|------|--|
| GOST |  |
|------|--|

|                  |  |
|------------------|--|
| cULus Recognized |  |
|------------------|--|

## Accessories

Accessories

## Fuse plug - ST-SILED 24-UK 4 - 0921037

### Accessories

Mounting material - ST-IL - 3039900

Operating decal for the ST terminal block



---

© Phoenix Contact 2013 - all rights reserved  
<http://www.phoenixcontact.com>