

## Ferrule - AI 16 -12 BU - 3200564

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)



Ferrule, Length: 24 mm, Color: blue


The figure shows the version AI 0.75-8 BU

### Product Features

- The AI 0,25.. ferrules can also be used to process 0.14 mm<sup>2</sup> conductors
- The insulation reliability of close connections is increased and the splicing of wires is prevented
- The ferrules with plastic sleeve are made from soft tin-plated electrolytic copper



### Key commercial data

Packing unit	1 PCE
Minimum order quantity	100 PCE
Catalog page	Page 305 (CL2-2011)
GTIN	 4 017918 094171
Custom tariff number	85369010
Country of origin	GERMANY

### Technical data

#### General

Length (b)	24 mm
Color	blue
Inflammability class according to UL 94	HB
Short-term temperature	120 °C
Max. permanent temperature	105 °C
Components	free from silicone and halogen
Material	E-CU

# Ferrule - AI 16 -12 BU - 3200564

## Technical data

### General

Sleeve length	12 mm
Inner dimension of the insulating collar (d)	8.8 mm
Ferrule diameter	5.8 mm
Insulating collar thickness	0.4 mm
Sleeve wall thickness	0.2 mm

## Classifications

### ETIM

ETIM 2.0	EC000005
ETIM 3.0	EC000005
ETIM 4.0	EC000005
ETIM 5.0	EC000005

### UNSPSC

UNSPSC 11	27121703
UNSPSC 12.01	27121703
UNSPSC 13.2	27121703
UNSPSC 6.01	30212109
UNSPSC 7.0901	27121703

### eCl@ss

eCl@ss 4.0	27060701
eCl@ss 4.1	27060701
eCl@ss 5.0	27400201
eCl@ss 5.1	27400201
eCl@ss 6.0	27400201
eCl@ss 7.0	27400201

## Approvals

### Approvals

---

#### Approvals

CSA / CSAus / GOST / cCSAus

---

#### Ex Approvals

# Ferrule - Al 16 -12 BU - 3200564


## Approvals

Approvals submitted

## Approval details



CSAus



cCSAus

## Drawings

Dimensioned drawing

