

Ferrule - AI-TWIN 2X 1,5 - 8 BK - 3200823

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)




Ferrule, Length: 16 mm, Color: black

Product Features

- Different versions of the individual TWIN ferrules can be selected for specific applications
- The TWIN ferrules provide a practical way of crimping two conductors in one ferrule
- These special ferrules allow chain bridges to be set up with ease



Key commercial data

Packing unit	1 PCE
Minimum order quantity	100 PCE
Catalog page	Page 310 (CL2-2011)
GTIN	 4 017918 094379
Custom tariff number	85369010
Country of origin	GERMANY

Technical data

General

Length (b)	16 mm
Color	black
Inflammability class according to UL 94	HB
Short-term temperature	120 °C
Max. permanent temperature	105 °C
Components	free from silicone and halogen
Material	E-CU
Sleeve length	8 mm

Ferrule - AI-TWIN 2X 1,5 - 8 BK - 3200823

Technical data

General

Inner dimension of the insulating collar (d)	3.6 mm
Ferrule diameter	2.3 mm
Insulating collar thickness	0.3 mm
Sleeve wall thickness	0.15 mm
Dimension d3	6.6 mm

Classifications

ETIM

ETIM 2.0	EC000005
ETIM 3.0	EC000005
ETIM 4.0	EC000005
ETIM 5.0	EC000005

UNSPSC

UNSPSC 11	27121703
UNSPSC 12.01	27121703
UNSPSC 13.2	27121703
UNSPSC 6.01	30212109
UNSPSC 7.0901	27121703

eCl@ss

eCl@ss 4.0	27060701
eCl@ss 4.1	27060701
eCl@ss 5.0	27400201
eCl@ss 5.1	27400201
eCl@ss 6.0	27400201
eCl@ss 7.0	27400201

Approvals

Approvals

Approvals

CSA / CSAus / GOST / cCSAus

Ex Approvals

Ferrule - AI-TWIN 2X 1,5 - 8 BK - 3200823

Approvals

Approvals submitted

Approval details



CSAus



cCSAus

Drawings

