

Ferrule - Al 1 - 8 RD -1000 - 3200904

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)



Ferrule, Length: 14 mm, Color: red


The figure shows the version Al 1-8 RD

Product Features

- The ferrules with plastic sleeve are made from soft tin-plated electrolytic copper
- The insulation reliability of close connections is increased and the splicing of wires is prevented
- The Al 0,25.. ferrules can also be used to process 0.14 mm² conductors



Key commercial data

Packing unit	1 PCE
Minimum order quantity	1000 PCE
Catalog page	Page 305 (CL2-2011)
GTIN	 4 017918 094454
Custom tariff number	85369010
Country of origin	GERMANY

Technical data

General

Length (b)	14 mm
Color	red
Inflammability class according to UL 94	HB
Short-term temperature	120 °C
Max. permanent temperature	105 °C
Components	free from silicone and halogen
Material	E-CU

Ferrule - AI 1 - 8 RD -1000 - 3200904

Technical data

General

Sleeve length	8 mm
Inner dimension of the insulating collar (d)	3 mm
Ferrule diameter	1.5 mm
Insulating collar thickness	0.3 mm
Sleeve wall thickness	0.15 mm

Classifications

ETIM

ETIM 2.0	EC000005
ETIM 3.0	EC000005
ETIM 4.0	EC000005
ETIM 5.0	EC000005

UNSPSC

UNSPSC 11	27121703
UNSPSC 12.01	27121703
UNSPSC 13.2	27121703
UNSPSC 6.01	30212109
UNSPSC 7.0901	27121703

eCl@ss

eCl@ss 4.0	27060701
eCl@ss 4.1	27060701
eCl@ss 5.0	27400201
eCl@ss 5.1	27400201
eCl@ss 6.0	27400201
eCl@ss 7.0	27400201

Approvals

Approvals

Approvals

CSA / CSAus / GOST / cCSAus



Ex Approvals

Ferrule - Al 1 - 8 RD -1000 - 3200904

Approvals

Approvals submitted

Approval details



Drawings

Dimensioned drawing

