

## Ferrule - Al 1,5 - 8 RD - 3201136

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)



Ferrule, Length: 14 mm, Color: red


The figure shows the version Al 1-8 RD

### Product Features

- The Al 0,25... can also be used to process 0.14 mm<sup>2</sup> conductors
- The ferrules with plastic sleeve are made from soft tin-plated electrolytic copper
- In terms of dimensions, they correspond to DIN 46228-4: 1990-09



### Key commercial data

Packing unit	1 PCE
Minimum order quantity	100 PCE
Catalog page	Page 307 (CL2-2011)
GTIN	 4 017918 094683
Custom tariff number	85369010
Country of origin	GERMANY

### Technical data

#### General

Length (b)	14 mm
Color	red
Inflammability class according to UL 94	HB
Short-term temperature	120 °C
Max. permanent temperature	105 °C
Components	free from silicone and halogen
Material	E-CU

# Ferrule - AI 1,5 - 8 RD - 3201136

## Technical data

### General

Sleeve length	8 mm
Inner dimension of the insulating collar (d)	3.4 mm
Ferrule diameter	1.8 mm
Insulating collar thickness	0.3 mm
Sleeve wall thickness	0.15 mm

## Classifications

### ETIM

ETIM 2.0	EC000005
ETIM 3.0	EC000005
ETIM 4.0	EC000005
ETIM 5.0	EC000005

### UNSPSC

UNSPSC 11	27121703
UNSPSC 12.01	27121703
UNSPSC 13.2	27121703
UNSPSC 6.01	30212109
UNSPSC 7.0901	27121703

### eCl@ss

eCl@ss 4.0	27060701
eCl@ss 4.1	27060701
eCl@ss 5.0	27400201
eCl@ss 5.1	27400201
eCl@ss 6.0	27400201
eCl@ss 7.0	27400201

## Approvals

### Approvals

---

#### Approvals

CSA / CSAus / GOST / cCSAus

---





#### Ex Approvals

# Ferrule - Al 1,5 - 8 RD - 3201136

## Approvals

Approvals submitted

## Approval details



## Drawings

Dimensioned drawing

