

## Ferrule - AI 0,34- 8 TQ - 3203066

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)



Ferrule, Length: 12.5 mm, Color: turquoise


The figure shows the version AI 2,5-12 BU

### Product Features

- The AI 0,25... can also be used to process 0.14 mm<sup>2</sup> conductors
- The ferrules with plastic sleeve are made from soft tin-plated electrolytic copper
- In terms of dimensions, they correspond to DIN 46228-4: 1990-09



### Key commercial data

|                        |   |
|------------------------|---|
| Packing unit           | 1 PCE   |
| Minimum order quantity | 100 PCE   |
| Catalog page           | Page 307 (CL2-2011)   |
| GTIN                   | <br>4 046356 013017 |
| Custom tariff number   | 85369010  |
| Country of origin      | GERMANY   |

### Technical data

#### General

|   |                                |
|---|--------------------------------|
| Length (b)                              | 12.5 mm                        |
| Color                                   | turquoise                      |
| Inflammability class according to UL 94 | HB                             |
| Short-term temperature                  | 120 °C                         |
| Max. permanent temperature              | 105 °C                         |
| Components                              | free from silicone and halogen |
| Material                                | E-CU                           |

## Ferrule - AI 0,34- 8 TQ - 3203066

### Technical data

#### General

|  |         |
|--|---------|
| Sleeve length                                | 8 mm    |
| Inner dimension of the insulating collar (d) | 2 mm    |
| Ferrule diameter                             | 0.8 mm  |
| Insulating collar thickness                  | 0.25 mm |
| Sleeve wall thickness                        | 0.15 mm |

### Classifications

#### ETIM

|          |          |
|----------|----------|
| ETIM 2.0 | EC000005 |
| ETIM 3.0 | EC000005 |
| ETIM 4.0 | EC000005 |
| ETIM 5.0 | EC000005 |

#### UNSPSC

|               |          |
|---------------|----------|
| UNSPSC 11     | 27121703 |
| UNSPSC 12.01  | 27121703 |
| UNSPSC 13.2   | 27121703 |
| UNSPSC 6.01   | 30212109 |
| UNSPSC 7.0901 | 27121703 |

#### eCl@ss

|            |          |
|------------|----------|
| eCl@ss 4.0 | 27060701 |
| eCl@ss 4.1 | 27060701 |
| eCl@ss 5.0 | 27400201 |
| eCl@ss 5.1 | 27400201 |
| eCl@ss 6.0 | 27400201 |
| eCl@ss 7.0 | 27400201 |

### Approvals

#### Approvals

---

#### Approvals

CSA / CSAus / GOST / cCSAus

---

#### Ex Approvals

## Ferrule - Al 0,34- 8 TQ - 3203066

### Approvals

Approvals submitted

### Approval details

CSA 

CSAus

GOST 

cCSAus

### Drawings

Dimensioned drawing

