

## Fuse plug - P-FU 5X20 LED 24 - 3036819

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)



Fuse plug with LED for 12 - 30 V DC, 0.31 - 0.95 mA, width 6.2 mm, color black

The illustration shows the version without light indicator

### Product Features

- Large-surface labeling option
- Test contacts on both sides of the fuse
- Versions with bipolar defect indicator
- Can be used for overload/short-circuit protection



### Key commercial data

Packing unit	1 PCE
Minimum order quantity	10 PCE
Catalog page	Page 399 (CL1-2011)
GTIN	 4 017918 943905
Custom tariff number	85366990
Country of origin	POLAND

### Technical data

#### General

Note	Prior to replacing the cartridge fuse, disconnect the fuse connector from the basic terminal block.
Color	black
Insulating material	PA
Inflammability class according to UL 94	V0

#### Dimensions

# Fuse plug - P-FU 5X20 LED 24 - 3036819

## Technical data

### Dimensions

Width	6.2 mm
Length	28 mm

### Technical data

Nominal current $I_N$	0.95 mA
Nominal voltage $U_N$	24 V (if used as disconnect terminal block. With fuse, the voltage is determined by the light indicator used.)
Nominal voltage $U_N$	24 V (if used as fuse terminal block)

## Classifications

### ETIM

ETIM 2.0	EC000897
ETIM 3.0	EC000897
ETIM 4.0	EC002018
ETIM 5.0	EC002018

### UNSPSC

UNSPSC 11	39121409
UNSPSC 12.01	39121409
UNSPSC 13.2	39121409
UNSPSC 6.01	30211811
UNSPSC 7.0901	39121409

### eCl@ss

eCl@ss 4.0	27141199
eCl@ss 4.1	27141199
eCl@ss 5.0	27141145
eCl@ss 5.1	27141145
eCl@ss 6.0	27141149
eCl@ss 7.0	27141149

## Approvals

### Approvals

---

Approvals

CSA

---

# Fuse plug - P-FU 5X20 LED 24 - 3036819


## Approvals

Ex Approvals

---


Approvals submitted

## Approval details

CSA 	
Nominal current I <sub>N</sub>	10 A
Nominal voltage U <sub>N</sub>	24 V

## Drawings


Application drawing



Fuse terminal blocks in interconnected arrangement, block consisting of 5 fuse terminal blocks

## Fuse plug - P-FU 5X20 LED 24 - 3036819

Application drawing



Fuse terminal block in single arrangement,  
block consisting of one fuse terminal block and 4 feed-through terminal blocks