

product type designation



C-PLUG

C-plug, removable data storage medium For simple device replacement in case of fault, for recording configuration or configuration and application data, can be used in the following SIMATIC NET products with C-plug slot: SCALANCE XC-200, XP-200, XM-400, XR-500, M-800, W-700, SC-600 and S615

ambient conditions

ambient temperature	
<ul style="list-style-type: none"> during operation during storage during transport 	<p>-40 ... +75 °C</p> <p>-40 ... +80 °C</p> <p>-40 ... +80 °C</p>
relative humidity	
<ul style="list-style-type: none"> at 25 °C / without condensation / during operation / maximum 	95 %
protection class IP	IP20

design, dimensions and weights

width	24.3 mm
height	17 mm
depth	8.1 mm
net weight	5 g
design of the removable storage	
<ul style="list-style-type: none"> C-PLUG KEY-PLUG 	<p>Yes</p> <p>No</p>
product feature / conformal coating	No

product features, product functions, product components / general

storage capacity	256 Mibyte
------------------	------------

standards, specifications, approvals

reference code	
<ul style="list-style-type: none"> according to IEC 81346-2:2019 	CFA

further information / internet-Links

Internet-Link	
<ul style="list-style-type: none"> to website: TIA Selection Tool to web page: selection aid TIA Selection Tool to the website: IWLAN to website: Industrial communication to website: Industry Mall to website: Information and Download Center to website: Image database to website: CAx-Download-Manager to website: Industry Online Support 	<p>http://www.siemens.com/tia-selection-tool</p> <p>http://www.siemens.com/snst</p> <p>http://www.siemens.com/iwlan</p> <p>http://www.siemens.com/simatic-net</p> <p>https://mall.industry.siemens.com</p> <p>http://www.siemens.com/industry/infocenter</p> <p>http://automation.siemens.com/bilddb</p> <p>http://www.siemens.com/cax</p> <p>https://support.industry.siemens.com</p>

last modified:

12/18/2020