



SIMATIC S7-1500T, CPU 1511TF-1 PN, Central processing unit with Work memory 225 KB for program and 1 MB for data, 1st interface: PROFINET IRT with 2-port switch, 60 ns bit performance, SIMATIC Memory Card required

| General information | |
|--|--|
| Product type designation | CPU 1511TF-1 PN |
| HW functional status | FS04 |
| Firmware version | V2.9 |
| Product function | |
| <ul style="list-style-type: none"> I&M data | Yes; I&M0 to I&M3 |
| <ul style="list-style-type: none"> Isochronous mode | Yes; Distributed and central; with minimum OB 6x cycle of 625 μ s (distributed) and 1 ms (central) |
| Engineering with | |
| <ul style="list-style-type: none"> STEP 7 TIA Portal configurable/integrated from version | V17 (FW V2.9) / V14 (FW V2.0) or higher |
| Configuration control | |
| via dataset | Yes |
| Display | |
| Screen diagonal [cm] | 3.45 cm |
| Control elements | |
| Number of keys | 6 |
| Mode selector switch | 1 |
| Supply voltage | |
| Rated value (DC) | 24 V |
| permissible range, lower limit (DC) | 19.2 V |
| permissible range, upper limit (DC) | 28.8 V |
| Reverse polarity protection | Yes |
| Mains buffering | |
| <ul style="list-style-type: none"> Mains/voltage failure stored energy time | 5 ms |
| <ul style="list-style-type: none"> Repeat rate, min. | 1/s |
| Input current | |
| Current consumption (rated value) | 0.7 A |
| Inrush current, max. | 1.9 A; Rated value |
| I^2t | 0.02 A ² ·s |
| Power | |
| Infeed power to the backplane bus | 10 W |
| Power consumption from the backplane bus (balanced) | 5.5 W |
| Power loss | |
| Power loss, typ. | 5.7 W |
| Memory | |
| Number of slots for SIMATIC memory card | 1 |
| SIMATIC memory card required | Yes |
| Work memory | |

| | |
|--|---|
| <ul style="list-style-type: none"> integrated (for program) | 225 kbyte |
| <ul style="list-style-type: none"> integrated (for data) | 1 Mbyte |
| Load memory | |
| <ul style="list-style-type: none"> Plug-in (SIMATIC Memory Card), max. | 32 Gbyte |
| Backup | |
| <ul style="list-style-type: none"> maintenance-free | Yes |
| CPU processing times | |
| for bit operations, typ. | 60 ns |
| for word operations, typ. | 72 ns |
| for fixed point arithmetic, typ. | 96 ns |
| for floating point arithmetic, typ. | 384 ns |
| CPU-blocks | |
| Number of elements (total) | 4 000; Blocks (OB, FB, FC, DB) and UDTs |
| DB | |
| <ul style="list-style-type: none"> Number range | 1 ... 60 999; subdivided into: number range that can be used by the user: 1 ... 59 999, and number range of DBs created via SFC 86: 60 000 ... 60 999 |
| <ul style="list-style-type: none"> Size, max. | 1 Mbyte; For DBs with absolute addressing, the max. size is 64 KB |
| FB | |
| <ul style="list-style-type: none"> Number range | 0 ... 65 535 |
| <ul style="list-style-type: none"> Size, max. | 150 kbyte |
| FC | |
| <ul style="list-style-type: none"> Number range | 0 ... 65 535 |
| <ul style="list-style-type: none"> Size, max. | 150 kbyte |
| OB | |
| <ul style="list-style-type: none"> Size, max. | 150 kbyte |
| <ul style="list-style-type: none"> Number of free cycle OBs | 100 |
| <ul style="list-style-type: none"> Number of time alarm OBs | 20 |
| <ul style="list-style-type: none"> Number of delay alarm OBs | 20 |
| <ul style="list-style-type: none"> Number of cyclic interrupt OBs | 20; With minimum OB 3x cycle of 500 µs |
| <ul style="list-style-type: none"> Number of process alarm OBs | 50 |
| <ul style="list-style-type: none"> Number of DPV1 alarm OBs | 3 |
| <ul style="list-style-type: none"> Number of isochronous mode OBs | 2 |
| <ul style="list-style-type: none"> Number of technology synchronous alarm OBs | 2 |
| <ul style="list-style-type: none"> Number of startup OBs | 100 |
| <ul style="list-style-type: none"> Number of asynchronous error OBs | 4 |
| <ul style="list-style-type: none"> Number of synchronous error OBs | 2 |
| <ul style="list-style-type: none"> Number of diagnostic alarm OBs | 1 |
| Nesting depth | |
| <ul style="list-style-type: none"> per priority class | 24; Up to 8 possible for F-blocks |
| Counters, timers and their retentivity | |
| S7 counter | |
| <ul style="list-style-type: none"> Number | 2 048 |
| Retentivity | |
| — adjustable | Yes |
| IEC counter | |
| <ul style="list-style-type: none"> Number | Any (only limited by the main memory) |
| Retentivity | |
| — adjustable | Yes |
| S7 times | |
| <ul style="list-style-type: none"> Number | 2 048 |
| Retentivity | |
| — adjustable | Yes |
| IEC timer | |
| <ul style="list-style-type: none"> Number | Any (only limited by the main memory) |
| Retentivity | |
| — adjustable | Yes |
| Data areas and their retentivity | |
| Retentive data area (incl. timers, counters, flags), max. | 128 kbyte; In total; available retentive memory for bit memories, timers, counters, DBs, and technology data (axes): 88 KB |

| | |
|---|---|
| Extended retentive data area (incl. timers, counters, flags), max. | 1 Mbyte; When using PS 6 0W 24/48/60 V DC HF |
| Flag | |
| <ul style="list-style-type: none"> • Size, max. • Number of clock memories | 16 kbyte 8; 8 clock memory bit, grouped into one clock memory byte |
| Data blocks | |
| <ul style="list-style-type: none"> • Retentivity adjustable • Retentivity preset | Yes No |
| Local data | |
| <ul style="list-style-type: none"> • per priority class, max. | 64 kbyte; max. 16 KB per block |
| Address area | |
| Number of IO modules | 1 024; max. number of modules / submodules |
| I/O address area | |
| <ul style="list-style-type: none"> • Inputs • Outputs | 32 kbyte; All inputs are in the process image 32 kbyte; All outputs are in the process image |
| per integrated IO subsystem | |
| <ul style="list-style-type: none"> — Inputs (volume) — Outputs (volume) | 8 kbyte 8 kbyte |
| per CM/CP | |
| <ul style="list-style-type: none"> — Inputs (volume) — Outputs (volume) | 8 kbyte 8 kbyte |
| Subprocess images | |
| <ul style="list-style-type: none"> • Number of subprocess images, max. | 32 |
| Hardware configuration | |
| Number of distributed IO systems | 32; A distributed I/O system is characterized not only by the integration of distributed I/O via PROFINET or PROFIBUS communication modules, but also by the connection of I/O via AS-i master modules or links (e.g. IE/PB-Link) |
| Number of DP masters | |
| <ul style="list-style-type: none"> • Via CM | 4; A maximum of 4 CMs/CPs (PROFIBUS, PROFINET, Ethernet) can be inserted in total |
| Number of IO Controllers | |
| <ul style="list-style-type: none"> • integrated • Via CM | 1 4; A maximum of 4 CMs/CPs (PROFIBUS, PROFINET, Ethernet) can be inserted in total |
| Rack | |
| <ul style="list-style-type: none"> • Modules per rack, max. • Number of lines, max. | 32; CPU + 31 modules 1 |
| PtP CM | |
| <ul style="list-style-type: none"> • Number of PtP CMs | the number of connectable PtP CMs is only limited by the number of available slots |
| Time of day | |
| Clock | |
| <ul style="list-style-type: none"> • Type • Backup time • Deviation per day, max. | Hardware clock 6 wk; At 40 °C ambient temperature, typically 10 s; Typ.: 2 s |
| Operating hours counter | |
| <ul style="list-style-type: none"> • Number | 16 |
| Clock synchronization | |
| <ul style="list-style-type: none"> • supported • in AS, master • in AS, slave • on Ethernet via NTP | Yes Yes Yes Yes |
| Interfaces | |
| Number of PROFINET interfaces | 1 |
| 1. Interface | |
| Interface types | |
| <ul style="list-style-type: none"> • RJ 45 (Ethernet) • Number of ports • integrated switch | Yes; X1 2 Yes |
| Protocols | |

| | |
|---|--|
| <ul style="list-style-type: none"> • IP protocol • PROFINET IO Controller • PROFINET IO Device • SIMATIC communication • Open IE communication • Web server • Media redundancy | <p>Yes; IPv4</p> <p>Yes</p> <p>Yes</p> <p>Yes</p> <p>Yes; Optionally also encrypted</p> <p>Yes</p> <p>Yes</p> |
| PROFINET IO Controller | |
| Services | |
| — PG/OP communication | Yes |
| — Isochronous mode | Yes |
| — Direct data exchange | Yes; Requirement: IRT and isochronous mode (MRPD optional) |
| — IRT | Yes |
| — PROFIenergy | Yes; per user program |
| — Prioritized startup | Yes; Max. 32 PROFINET devices |
| — Number of connectable IO Devices, max. | 128; In total, up to 256 distributed I/O devices can be connected via AS-i, PROFIBUS or PROFINET |
| — Of which IO devices with IRT, max. | 64 |
| — Number of connectable IO Devices for RT, max. | 128 |
| — of which in line, max. | 128 |
| — Number of IO Devices that can be simultaneously activated/deactivated, max. | 8; in total across all interfaces |
| — Number of IO Devices per tool, max. | 8 |
| — Updating times | The minimum value of the update time also depends on communication share set for PROFINET IO, on the number of IO devices, and on the quantity of configured user data |
| Update time for IRT | |
| — for send cycle of 250 µs | 250 µs to 4 ms; Note: In the case of IRT with isochronous mode, the minimum update time of 625 µs of the isochronous OB is decisive |
| — for send cycle of 500 µs | 500 µs to 8 ms; Note: In the case of IRT with isochronous mode, the minimum update time of 625 µs of the isochronous OB is decisive |
| — for send cycle of 1 ms | 1 ms to 16 ms |
| — for send cycle of 2 ms | 2 ms to 32 ms |
| — for send cycle of 4 ms | 4 ms to 64 ms |
| — With IRT and parameterization of "odd" send cycles | Update time = set "odd" send clock (any multiple of 125 µs: 375 µs, 625 µs ... 3 875 µs) |
| Update time for RT | |
| — for send cycle of 250 µs | 250 µs to 128 ms |
| — for send cycle of 500 µs | 500 µs to 256 ms |
| — for send cycle of 1 ms | 1 ms to 512 ms |
| — for send cycle of 2 ms | 2 ms to 512 ms |
| — for send cycle of 4 ms | 4 ms to 512 ms |
| PROFINET IO Device | |
| Services | |
| — PG/OP communication | Yes |
| — Isochronous mode | No |
| — IRT | Yes |
| — PROFIenergy | Yes; per user program |
| — Shared device | Yes |
| — Number of IO Controllers with shared device, max. | 4 |
| — activation/deactivation of I-devices | Yes; per user program |
| — Asset management record | Yes; per user program |
| Interface types | |
| RJ 45 (Ethernet) | |
| • 100 Mbps | Yes |
| • Autonegotiation | Yes |
| • Autocrossing | Yes |
| • Industrial Ethernet status LED | Yes |
| Protocols | |
| PROFIsafe | Yes; V2.4 / V2.6 |

| | |
|---|---|
| Number of connections | |
| <ul style="list-style-type: none"> • Number of connections, max. • Number of connections reserved for ES/HMI/web • Number of connections via integrated interfaces • Number of S7 routing paths | <p>96; via integrated interfaces of the CPU and connected CPs / CMs</p> <p>10</p> <p>64</p> <p>16</p> |
| Redundancy mode | |
| <ul style="list-style-type: none"> • H-Sync forwarding | Yes |
| Media redundancy | |
| <ul style="list-style-type: none"> — Media redundancy — MRP — MRP interconnection, supported — MRPD — Switchover time on line break, typ. — Number of stations in the ring, max. | <p>only via 1st interface (X1)</p> <p>Yes; MRP Automanager according to IEC 62439-2 Edition 2.0, MRP Manager; MRP Client</p> <p>Yes; as MRP ring node according to IEC 62439-2 Edition 3.0</p> <p>Yes; Requirement: IRT</p> <p>200 ms; For MRP, bumpless for MRPD</p> <p>50</p> |
| SIMATIC communication | |
| <ul style="list-style-type: none"> • PG/OP communication • S7 routing • S7 communication, as server • S7 communication, as client • User data per job, max. | <p>Yes; encryption with TLS V1.3 pre-selected</p> <p>Yes</p> <p>Yes</p> <p>Yes</p> <p>See online help (S7 communication, user data size)</p> |
| Open IE communication | |
| <ul style="list-style-type: none"> • TCP/IP <ul style="list-style-type: none"> — Data length, max. — several passive connections per port, supported • ISO-on-TCP (RFC1006) <ul style="list-style-type: none"> — Data length, max. • UDP <ul style="list-style-type: none"> — Data length, max. — UDP multicast • DHCP • DNS • SNMP • DCP • LLDP • Encryption | <p>Yes</p> <p>64 kbyte</p> <p>Yes</p> <p>Yes</p> <p>64 kbyte</p> <p>Yes</p> <p>2 kbyte; 1 472 bytes for UDP broadcast</p> <p>Yes; Max. 5 multicast circuits</p> <p>Yes</p> <p>Yes</p> <p>Yes</p> <p>Yes</p> <p>Yes</p> <p>Yes</p> <p>Yes; Optional</p> |
| Web server | |
| <ul style="list-style-type: none"> • HTTP • HTTPS | <p>Yes; Standard and user pages</p> <p>Yes; Standard and user pages</p> |
| OPC UA | |
| <ul style="list-style-type: none"> • Runtime license required • OPC UA Client <ul style="list-style-type: none"> — Application authentication — Security policies — User authentication — Number of connections, max. — Number of nodes of the client interfaces, max. — Number of elements for one call of OPC-UA_NodeGetHandleList/OPC-UA_ReadList/C max. — Number of elements for one call of OPC-UA_NameSpaceGetIndexList, max. — Number of elements for one call of OPC-UA_MethodGetHandleList, max. — Number of simultaneous calls of the client instructions per connection (except OPC-UA_ReadList,OPC-UA_WriteList,OPC-UA_M max. — Number of simultaneous calls of the client instructions OPC-UA_ReadList,OPC-UA_WriteList and | <p>Yes; "Small" license required</p> <p>Yes</p> <p>Yes</p> <p>Available security policies: None, Basic128Rsa15, Basic256Rsa15, Basic256Sha256</p> <p>"anonymous" or by user name & password</p> <p>4</p> <p>1 000</p> <p>300</p> <p>20</p> <p>100</p> <p>1</p> <p>5</p> |

| | |
|--|--|
| OPC-UA_MethodCall, max. | |
| — Number of registerable nodes, max. | 5 000 |
| — Number of registerable method calls of OPC-UA_MethodCall, max. | 100 |
| — Number of inputs/outputs when calling OPC-UA_MethodCall, max. | 20 |
| ● OPC UA Server | Yes; Data access (read, write, subscribe), method call, custom address space |
| — Application authentication | Yes |
| — Security policies | Available security policies: None, Basic128Rsa15, Basic256Rsa15, Basic256Sha256 |
| — User authentication | "anonymous" or by user name & password |
| — GDS support (certificate management) | Yes |
| — Number of sessions, max. | 32 |
| — Number of accessible variables, max. | 50 000 |
| — Number of registerable nodes, max. | 10 000 |
| — Number of subscriptions per session, max. | 20 |
| — Sampling interval, min. | 100 ms |
| — Publishing interval, min. | 500 ms |
| — Number of server methods, max. | 20 |
| — Number of inputs/outputs per server method, max. | 20 |
| — Number of monitored items, max. | 1 000; for 1 s sampling interval and 1 s send interval |
| — Number of server interfaces, max. | 10 of each "Server interfaces" / "Companion specification" type and 20 of the type "Reference namespace" |
| — Number of nodes for user-defined server interfaces, max. | 1 000 |
| ● Alarms and Conditions | Yes |
| — Number of program alarms | 100 |
| — Number of alarms for system diagnostics | 50 |
| Further protocols | |
| ● MODBUS | Yes; MODBUS TCP |
| Isochronous mode | |
| Equidistance | Yes |
| S7 message functions | |
| Number of login stations for message functions, max. | 32 |
| Program alarms | Yes |
| Number of configurable program messages, max. | 5 000; Program messages are generated by the "Program_Alarm" block, ProDiag or GRAPH |
| Number of loadable program messages in RUN, max. | 2 500 |
| Number of simultaneously active program alarms | |
| ● Number of program alarms | 600 |
| ● Number of alarms for system diagnostics | 100 |
| ● Number of alarms for motion technology objects | 80 |
| Test commissioning functions | |
| Joint commission (Team Engineering) | Yes; Parallel online access possible for up to 5 engineering systems |
| Status block | Yes; Up to 8 simultaneously (in total across all ES clients) |
| Single step | No |
| Number of breakpoints | 8 |
| Status/control | |
| ● Status/control variable | Yes; without fail-safe |
| ● Variables | inputs/outputs, bit memories, DBs, peripheral I/Os (without fail-safe), times, counters |
| ● Number of variables, max. | |
| — of which status variables, max. | 200; per job |
| — of which control variables, max. | 200; per job |
| Forcing | |
| ● Forcing | Yes; without fail-safe |
| ● Forcing, variables | peripheral inputs/outputs (without fail-safe) |
| ● Number of variables, max. | 200 |
| Diagnostic buffer | |
| ● present | Yes |

| | |
|--|---|
| <ul style="list-style-type: none"> • Number of entries, max. 1 000 — of which powerfail-proof 500 | |
| Traces | |
| <ul style="list-style-type: none"> • Number of configurable Traces | 4; Up to 512 KB of data per trace are possible |
| Interrupts/diagnostics/status information | |
| Diagnostics indication LED | |
| <ul style="list-style-type: none"> • RUN/STOP LED | Yes |
| <ul style="list-style-type: none"> • ERROR LED | Yes |
| <ul style="list-style-type: none"> • MAINT LED | Yes |
| <ul style="list-style-type: none"> • Connection display LINK TX/RX | Yes |
| Supported technology objects | |
| Motion Control | Yes; Note: The number of technology objects affects the cycle time of the PLC program; selection guide via the TIA Selection Tool |
| <ul style="list-style-type: none"> • Number of available Motion Control resources for technology objects | 800 |
| <ul style="list-style-type: none"> • Required Motion Control resources | |
| <ul style="list-style-type: none"> — per speed-controlled axis | 40 |
| <ul style="list-style-type: none"> — per positioning axis | 80 |
| <ul style="list-style-type: none"> — per synchronous axis | 160 |
| <ul style="list-style-type: none"> — per external encoder | 80 |
| <ul style="list-style-type: none"> — per output cam | 20 |
| <ul style="list-style-type: none"> — per cam track | 160 |
| <ul style="list-style-type: none"> — per probe | 40 |
| <ul style="list-style-type: none"> • Number of available Extended Motion Control resources for technology objects | 40 |
| <ul style="list-style-type: none"> • Required Extended Motion Control resources | |
| <ul style="list-style-type: none"> — per cam (1 000 points and 50 segments) | 2 |
| <ul style="list-style-type: none"> — per cam (10 000 points and 50 segments) | 20 |
| <ul style="list-style-type: none"> — for each set of kinematics | 30 |
| <ul style="list-style-type: none"> — Per leading axis proxy | 3 |
| <ul style="list-style-type: none"> • Positioning axis | |
| <ul style="list-style-type: none"> — Number of positioning axes at motion control cycle of 4 ms (typical value) | 5 |
| <ul style="list-style-type: none"> — Number of positioning axes at motion control cycle of 8 ms (typical value) | 10 |
| Controller | |
| <ul style="list-style-type: none"> • PID_Compact | Yes; Universal PID controller with integrated optimization |
| <ul style="list-style-type: none"> • PID_3Step | Yes; PID controller with integrated optimization for valves |
| <ul style="list-style-type: none"> • PID-Temp | Yes; PID controller with integrated optimization for temperature |
| Counting and measuring | |
| <ul style="list-style-type: none"> • High-speed counter | Yes |
| Standards, approvals, certificates | |
| Highest safety class achievable in safety mode | |
| <ul style="list-style-type: none"> • Performance level according to ISO 13849-1 | PLe |
| <ul style="list-style-type: none"> • SIL acc. to IEC 61508 | SIL 3 |
| Probability of failure (for service life of 20 years and repair time of 100 hours) | |
| <ul style="list-style-type: none"> — Low demand mode: PFDavg in accordance with SIL3 | < 2.00E-05 |
| <ul style="list-style-type: none"> — High demand/continuous mode: PFH in accordance with SIL3 | < 1.00E-09 |
| Ambient conditions | |
| Ambient temperature during operation | |
| <ul style="list-style-type: none"> • horizontal installation, min. | 0 °C |
| <ul style="list-style-type: none"> • horizontal installation, max. | 60 °C; Display: 50 °C, at an operating temperature of typically 50 °C, the display is switched off |
| <ul style="list-style-type: none"> • vertical installation, min. | 0 °C |
| <ul style="list-style-type: none"> • vertical installation, max. | 40 °C; Display: 40 °C, at an operating temperature of typically 40 °C, the display is switched off |
| Ambient temperature during storage/transportation | |
| <ul style="list-style-type: none"> • min. | -40 °C |
| <ul style="list-style-type: none"> • max. | 70 °C |
| Altitude during operation relating to sea level | |

- Installation altitude above sea level, max.

5 000 m; Restrictions for installation altitudes > 2 000 m, see manual

configuration / header

configuration / programming / header

Programming language

| | |
|---------|---------------------|
| — LAD | Yes; incl. failsafe |
| — FBD | Yes; incl. failsafe |
| — STL | Yes |
| — SCL | Yes |
| — GRAPH | Yes |

Know-how protection

| | |
|---|-----|
| • User program protection/password protection | Yes |
| • Copy protection | Yes |
| • Block protection | Yes |

Access protection

| | |
|---|---|
| • protection of confidential configuration data | Yes |
| • Password for display | Yes |
| • Protection level: Write protection | Yes; Specific write protection both for Standard and for Failsafe |
| • Protection level: Read/write protection | Yes |
| • Protection level: Write protection for Failsafe | Yes |
| • Protection level: Complete protection | Yes |

programming / cycle time monitoring / header

| | |
|---------------|-------------------------------|
| • lower limit | adjustable minimum cycle time |
| • upper limit | adjustable maximum cycle time |

Dimensions

| | |
|--------|--------|
| Width | 35 mm |
| Height | 147 mm |
| Depth | 129 mm |

Weights

| | |
|-----------------|-------|
| Weight, approx. | 430 g |
|-----------------|-------|

last modified:

11/10/2021 