## **SIEMENS**

Data sheet 3VA9978-0AA11



auxiliary switch changeover contacts type HP (14mm) accessory for: 3VA4/5/6

Model		
product brand name	SENTRON	
product designation	auxiliary switch	
Product version	Accessories for 3VA circuit breakers	
Accessories	Auxiliary switch	
General technical data		
Degree of pollution	3	
Overvoltage category	III	
Voltage		
Tension assignée de tenue aux chocs	4 kV	
operating voltage / at AC / acc. to CSA and UL	600 V	
operating voltage / at DC / acc. to CSA and UL	250 V	
Rated operational voltage Ue at AC 50 Hz	600 V	
Rated operational voltage Ue with DC	250 V	
Current		
Thermal current limit Ith	10 A	
operational current		
• at AC-12 / at 12 V	10 A	
• at AC-12 / at 24 V	10 A	
• at AC-12 / at 48 V	10 A	
• at AC-12 / at 125 V	10 A	
• at AC-12 / at 220/240 V	10 A	
• at AC-12 / at 380/400 V	6 A	
• at AC-12 / at 400 V	6 A	
• at AC-12 / at 600 V	2 A	
• at DC-12 / at 12 V	6 A	
• at DC-12 / at 24 V	6 A	
• at DC-12 / at 48 V	2 A	
• at DC-12 / at 110 V	0.6 A	
• at DC-12 / at 250 V	0.3 A	
• at DC-13 / at 12 V	3 A	
• at DC-13 / at 24 V	3 A	
• at DC-13 / at 48 V	0.8 A	
• at DC-13 / at 110 V	0.2 A	
• at DC-13 / at 250 V	0.1 A	
• at AC-15 / at 12 V	6 A	
• at AC-15 / at 24 V	6 A	
• at AC-15 / at 48 V	6 A	
• at AC-15 / at 125 V	6 A	

• at AC-15 / at 220/240 V	6 A
• at AC-15 / at 380/400 V	2 A
• at AC-15 / at 600 V	0.6 A
Mechanical Design	
tightening torque / with screw-type terminals / minimum	0.4 N·m
tightening torque / with screw-type terminals / maximum	0.5 N·m
Connections according IEC	
stripped length	15 mm
AWG number / as coded connectable conductor cross section / for auxiliary contacts	
• minimum	19
• maximum	14
Connetctions according UL	
stripped length [in]	0.6 in
tightening torque [lbf·in] / with screw-type terminals / minimum	3.5 lbf·in
tightening torque [lbf·in] / with screw-type terminals / maximum	4.4 lbf·in
Further information	

Information- and Downloadcenter (Catalogs, Brochures,...)

http://www.siemens.com/lowvoltage/catalogs

Industry Mall (Online ordering system)

https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3VA9978-0AA11

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

https://support.industry.siemens.com/cs/ww/en/ps/3VA9978-0AA11


Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...) <a href="http://www.automation.siemens.com/bilddb/cax\_en.aspx?mlfb=3VA9978-0AA11">http://www.automation.siemens.com/bilddb/cax\_en.aspx?mlfb=3VA9978-0AA11</a>


**CAx-Online-Generator** 


http://www.siemens.com/cax

**Tender specifications** 

http://www.siemens.com/specifications







12/20/2020 🖸

last modified:

3VA99780AA11 Page 3/4