SIEMENS

Data sheet

6GK1901-1BE00-0AA1

product type designation



IE FC RJ45 modular outlet (insert 2FE)

IE FC RJ45 modular outlet Base module with insert 2FE Interchangeable insert for 2 x 100 Mbit/s interface

transfer rate	
transfer rate	
 1 / for Industrial Ethernet 	10 Mbit/s
 2 / for Industrial Ethernet 	100 Mbit/s
interfaces	
number of electrical connections	
 for Industrial Ethernet FC TP cables 	1
 for network components or terminal equipment 	2
type of electrical connection	
 for Industrial Ethernet FC TP cables 	integrated insulation displacement contacts
 for FC RJ45 modular outlet insert 2FE 	2 x RJ45 socket (10/100 Mbit/s)
 FastConnect 	Yes
mechanical data	
material / of the enclosure	metal
number of reuses	10
design, dimensions and weights	
width	50 mm
height	115.25 mm
depth	58.95 mm
net weight	450 g
connectable cable cross-section	9.5 9.5
fastening method	
 35 mm top hat DIN rail mounting 	Yes
wall mounting	Yes
ambient conditions	
ambient temperature	
 during operation 	-20 +70 °C
 during storage 	-40 +80 °C
during transport	-40 +80 °C
relative humidity / at 25 $^{\circ}\text{C}$ / without condensation / during operation / maximum	95 %
protection class IP	IP40
product features, product functions, product components / general	
product feature	
• silicon-free	Yes
standards, specifications, approvals	
certificate of suitability	
RoHS conformity	Yes
product feature	Yes

 UL approval 	Yes
standard for structured cabling	Cat 6
further information / internet-Links	
Internet-Link	
 to website: Industrial communication 	http://www.siemens.com/simatic-net
to website: Industry Mall	https://mall.industry.siemens.com
 to website: Information and Download Center 	http://www.siemens.com/industry/infocenter
 to website: Selection guide for cables and connectors 	https://sie.ag/2QdlxcP
 to website: Image database 	http://automation.siemens.com/bilddb
 to website: CAx-Download-Manager 	http://www.siemens.com/cax
 to website: Industry Online Support 	https://support.industry.siemens.com

last modified: 6/30/2021 🖸