

product description



PROFIBUS bus connector, RS 485, Fast Connect, with programming port, 90°

SIMATIC DP, Connection plug for PROFIBUS up to 12 Mbit/s 90° cable outlet, 15.8x 72.2x 36.4 mm (WxHxD), Insulation displacement method FastConnect, With PG receptacle

suitability for use

for connecting PROFIBUS nodes to the PROFIBUS bus cable

### transfer rate

transfer rate / with PROFIBUS DP 9.6 kbit/s ... 12 Mbit/s

### interfaces

number of electrical connections	
• for PROFIBUS cables	2
• for network components or terminal equipment	1
type of electrical connection	
• for network components or terminal equipment	9-pin sub D connector
type of electrical connection / FastConnect	Yes

### mechanical data

design of terminating resistor	Resistor combination integrated and connectable via slide switch
material / of the enclosure	plastic
locking mechanism design	Screwed joint

### design, dimensions and weights

type of cable outlet	90 degree cable outlet
width	15.8 mm
height	72 mm
depth	36.4 mm
net weight	45 g

### ambient conditions

ambient temperature	
• during operation	-25 ... +60 °C
• during storage	-40 ... +70 °C
• during transport	-40 ... +70 °C
protection class IP	IP20

### product features, product functions, product components / general

product feature	
• silicon-free	Yes
product component	
• PG connection socket	Yes
• strain relief	Yes

### standards, specifications, approvals

certificate of suitability	
• RoHS conformity	Yes
• UL approval	Yes
reference code	

- acc. to IEC 81346-2

XF

#### further information / internet-Links

##### Internet-Link

- to website: Selection guide for cables and connectors

<https://sie.ag/2QdlxcP>

##### last modified:

9/15/2021 