SIEMENS

Data sheet

6GK5008-0BA10-1AB2



SCALANCE XB008 Unmanaged Industrial Ethernet Switch for 10/100 Mbit/s for setting up small star and line topologies; LED diagnostics, IP20, 24 V AC/DC power supply, with 8x 10/100 Mbit/s twisted pair ports with RJ45 sockets; Manual available as a download

product type designation	SCALANCE XB008
transfer rate	
transfer rate	10 Mbit/s, 100 Mbit/s
interfaces / for communication / integrated	
number of electrical connections	
 for network components or terminal equipment 	8; RJ45
number of 100 Mbit/s SC ports	
• for multimode	0
interfaces / other	
number of electrical connections	
 for power supply 	1
type of electrical connection	
 for power supply 	3-pole terminal block
supply voltage, current consumption, power loss	
type of voltage / 1 / of the supply voltage	DC
 supply voltage / 1 / rated value 	24 V
 power loss [W] / 1 / rated value 	2.88 W
 supply voltage / 1 / rated value 	19.2 28.8 V
 consumed current / 1 / maximum 	0.12 A
 type of electrical connection / 1 / for power supply 	3-pole terminal block
 product component / 1 / fusing at power supply input 	Yes
type of voltage / 2 / of the supply voltage	
 supply voltage / 2 / rated value 	19.2 28.8 V
ambient conditions	
ambient temperature	
 during operation 	-10 +60 °C
 during storage 	-40 +80 °C
during transport	-40 +80 °C
relative humidity	
 at 25 °C / without condensation / during operation / maximum 	95 %
protection class IP	IP20
design, dimensions and weights	
design	Box
width	45 mm
height	100 mm
depth	87 mm
net weight	0.18 kg
fastening method	

- 25 mm top hot DIN roll mounting	Voo	
35 mm top hat DIN rail mounting	Yes	
wall mounting S7 1500 rail mounting	Yes	
S7-1500 rail mounting	No	
product functions / management, configuration, engineeri	ng	
product function		
multiport mirroring	No	
• CoS	Yes	
PROFINET conformity class product function / switch-managed	No	
product functions / redundancy		
product function Parallel Redundancy Protocol (PRP)/operation in 	Yes	
the PRP-network	1 55	
 Parallel Redundancy Protocol (PRP)/Redundant Network Access (RNA) 	No	
standards, specifications, approvals		
standard		
• for FM	FM3611: Class 1, Divison 2, Group A, B, C, D / T4, CL.1, Zone 2, GP. IIC, T4	
 for safety / from CSA and UL 	UL 60950-1, CSA C22.2 No. 60950-1	
 for emitted interference 	EN 61000-6-4 (Class A)	
for interference immunity	EN 61000-6-2	
MTBF	214 у	
reference code		
• acc. to IEC 81346-2	KF	
 according to IEC 81346-2:2019 	KFE	
standards, specifications, approvals / CE		
certificate of suitability / CE marking	Yes	
standards, specifications, approvals / hazardous environn	nents	
standard / for hazardous zone	EN 60079-0:2009, EN60079-15:2010, II 3 G Ex nA IIC T4 Gc, KEMA 07ATEX0145 X	
certificate of suitability		
CCC / for hazardous zone according to GB standard	Yes	
standards, specifications, approvals / other		
certificate of suitability	EN 61000-6-2, EN 61000-6-4	
C-Tick	Yes	
KC approval	Yes	
further information / internet-Links		
Internet-Link		
 to web page: selection aid TIA Selection Tool 	http://www.siemens.com/tia-selection-tool	
to website: Industrial communication	http://www.siemens.com/simatic-net	
• to website: Industry Mall	https://mall.industry.siemens.com	
 to website: Information and Download Center 	http://www.siemens.com/industry/infocenter	
• to website: Image database	http://automation.siemens.com/bilddb	
to website: CAx-Download-Manager to website: Industry Opling Support	http://www.siemens.com/cax	
to website: Industry Online Support	https://support.industry.siemens.com	
security information		
security information	Siemens provides products and solutions with industrial security functions that support the secure operation of plants, solutions, machines, equipment and/or networks. They are important components in a holistic industrial security concept. With this in mind, Siemens' products and solutions undergo continuous development. Siemens recommends strongly that you regularly check for product updates. For the secure operation of Siemens products and solutions, it is necessary to take suitable preventive action(e.g. cell protection concept) and integrate each component into a holistic, state-of-the-art industrial security concept. Third-party products that may be in use should also be considered. For more information about industrial security, visit http://www.siemens.com/industrialsecurity. To stay informed about product updates as they occur, sign up for a product-specific newsletter. For more information, visit http://support.automation.siemens.com. (V3.4)	
last modified:	12/27/2021 🖸	