



Figure similar

SIMATIC DP, distributed I/O Field device interface DP/PA coupler Ex version Ex(IA) 110 mA Field coupler between PROFIBUS DP and field bus segments to IEC 61158-2, for example PROFIBUS PA, for extended temperature range Degree of protection IP20

General information	
Product description	FDC157 Ex [ia]
Supply voltage	
Rated value (DC)	24 V
permissible range, lower limit (DC)	20.4 V
permissible range, upper limit (DC)	28.8 V
Reverse polarity protection	Yes
Mains buffering	
<ul style="list-style-type: none"> Mains/voltage failure stored energy time 	5 ms
Input current	
Current consumption, max.	400 mA
Power loss	
Power loss, typ.	7 W
Interfaces	
PROFIBUS DP	
<ul style="list-style-type: none"> Transmission rate, max. Design of electrical connection 	45.45 kbit/s 9-pin sub D
PROFIBUS PA	
<ul style="list-style-type: none"> Transmission rate, max. Number of connectable PA field devices Current output to PA field devices, max. 	31.25 kbit/s 31 110 mA
Protocols	
PROFIBUS DP	Yes
PROFIBUS PA	Yes
Interrupts/diagnostics/status information	
Status indicator	No
Diagnostics function	Yes
Diagnostics indication LED	
<ul style="list-style-type: none"> Bus activity DP (yellow) Bus activity PA (yellow) Monitoring 24 V voltage supply ON (green) 	Yes Yes Yes
Ex(i) characteristics	
maximum values for connecting terminals for gas group IIC	
<ul style="list-style-type: none"> U_o (no-load voltage), max. I_o (short-circuit current), max. P_o (power output), max. U_m (voltage at non-intrinsically safe connecting terminals), max. 	15 V 247 mA 1.95 W 250 V; AC

Potential separation	
between PROFIBUS DP and all other circuit components	Yes
between PROFIBUS PA and all other circuit components	Yes
Isolation	
Isolation tested with	500 V AC
Degree and class of protection	
IP degree of protection	IP20
Ambient conditions	
Ambient temperature during operation	
• min.	-25 °C
• max.	60 °C
Ambient temperature during storage/transportation	
• min.	-40 °C
• max.	70 °C
Relative humidity	
• Operation, max.	95 %
Dimensions	
Width	80 mm
Height	125 mm
Depth	130 mm
Weights	
Weight, approx.	550 g
last modified:	12/7/2021 