# **SIEMENS**

### **Data sheet**

## 6GK7242-5DX30-0XE0

#### product type designation



#### CM 1242-5

Communication module CM 1242-5; for connection of SIMATIC S7-1200 to PROFIBUS as DP Slave module

transfer rate	
transfer rate	
<ul> <li>at the 1st interface / acc. to PROFIBUS</li> </ul>	9.6 kbit/s 12 Mbit/s
interfaces	
number of interfaces / acc. to Industrial Ethernet	0
number of electrical connections	
<ul> <li>at the 1st interface / acc. to PROFIBUS</li> </ul>	1
for power supply	0
type of electrical connection	
<ul> <li>at the 1st interface / acc. to PROFIBUS</li> </ul>	9-pin Sub-D socket (RS485)
supply voltage, current consumption, power loss	
type of voltage / of the supply voltage	DC
supply voltage / 1 / from backplane bus	5 V
consumed current	
from backplane bus / at DC / at 5 V / typical	0.15 A
power loss [W]	0.75 W
ambient conditions	_
ambient temperature	
<ul> <li>for vertical installation / during operation</li> </ul>	0 45 °C
<ul> <li>for horizontally arranged busbars / during operation</li> </ul>	0 55 °C
<ul> <li>during storage</li> </ul>	-40 +70 °C
during transport	-40 +70 °C
relative humidity	
at 25 °C / without condensation / during operation / maximum	95 %
protection class IP	IP20
design, dimensions and weights	
module format	Compact module S7-1200 single width
width	30 mm
height	100 mm
depth	75 mm
net weight	0.115 kg
fastening method	
<ul> <li>35 mm top hat DIN rail mounting</li> </ul>	Yes
<ul> <li>S7-300 rail mounting</li> </ul>	No
wall mounting	Yes
product features, product functions, product components	/ general
number of units	

• per CPU / maximum	3	
performance data / PROFIBUS DP		
service / as DP slave		
• DPV0	Yes	
• DPV1	Yes	
data volume		
<ul> <li>of the address range of the inputs / as DP slave / total</li> </ul>	240 byte	
<ul> <li>of the address range of the outputs / as DP slave / total</li> </ul>	240 byte	
performance data / telecontrol		
protocol / is supported		
• TCP/IP	No	
product functions / management, configuration, engineering		
configuration software		
• required	STEP 7 Basic/Professional	
standards, specifications, approvals / hazardous environments		
certificate of suitability / CCC / for hazardous zone according to GB standard	Yes	
further information / internet-Links		
Internet-Link		
<ul><li>to web page: selection aid TIA Selection Tool</li></ul>	http://www.siemens.com/tia-selection-tool	
<ul> <li>to website: Industrial communication</li> </ul>	http://www.siemens.com/simatic-net	
<ul><li>to website: Industry Mall</li></ul>	https://mall.industry.siemens.com	
<ul> <li>to website: Information and Download Center</li> </ul>	http://www.siemens.com/industry/infocenter	
<ul><li>to website: Image database</li></ul>	http://automation.siemens.com/bilddb	
<ul><li>to website: CAx-Download-Manager</li></ul>	http://www.siemens.com/cax	
<ul> <li>to website: Industry Online Support</li> </ul>	https://support.industry.siemens.com	
security information		
security information	Siemens provides products and solutions with industrial security functions that support the secure operation of plants, solutions, machines, equipment and/or networks. They are important components in a holistic industrial security concept. With this in mind, Siemens' products and solutions undergo continuous development. Siemens recommends strongly that you regularly check for product updates. For the secure operation of Siemens products and solutions, it is necessary to take suitable preventive action(e.g. cell protection concept) and integrate each component into a holistic, state-of-the-art industrial security concept. Third-party products that may be in use should also be considered. For more information about industrial security, visit http://www.siemens.com/industrialsecurity. To stay informed about product updates as they occur, sign up for a product-specific newsletter. For more information, visit http://support.automation.siemens.com. (V3.4)	
last modified:	8/3/2021 🖸	