



SIMATIC ET 200SP, BaseUnit BU20-P6+A2+4D, BU type C0, Push-in terminals, with 2 AUX terminals, New load group, WxH: 20 mmx117 mm

General information	
Product type designation	BU type C0
HW functional status	FS10 and higher
Supply voltage	
Rated value (DC)	See manual
<ul style="list-style-type: none"> For P1 and P2 bus For AUX bus for process terminals 	24 V 24 V; Equal potential group to P1/P2 bus or PE 24 V
Rated value (AC)	See manual
<ul style="list-style-type: none"> For P1 and P2 bus For AUX bus for process terminals 	230 V 230 V; Equal potential group to P1/P2 bus or PE 230 V
external protection for power supply lines	Yes; 10 A miniature circuit breaker with type B or C tripping characteristic for the respective rated supply voltage
Mains filter	
<ul style="list-style-type: none"> integrated 	No
Current carrying capacity	
up to 60 °C, max.	10 A
For P1 and P2 bus, max.	10 A
For AUX bus, max.	10 A
For process terminals, max.	5 A; 10 A for process terminals 5 and 6
Hardware configuration	
Automatic encoding	Yes
Slots	
<ul style="list-style-type: none"> Number of slots 	1
Potential separation	
between backplane bus and supply voltage	Yes
between process terminals and supply voltage	Yes
between power bus and supply voltage	No
Isolation	
Isolation tested with	3 100 V DC
Ambient conditions	
Ambient temperature during operation	
<ul style="list-style-type: none"> horizontal installation, min. horizontal installation, max. vertical installation, min. vertical installation, max. 	-30 °C 60 °C -30 °C 50 °C
Altitude during operation relating to sea level	
<ul style="list-style-type: none"> Installation altitude above sea level, max. 	2 000 m; On request: Installation altitudes greater than 2 000 m

Accessories	
Color coding labels	
<ul style="list-style-type: none"> • for process terminals 	CC51, CC52
<ul style="list-style-type: none"> • for AUX terminals 	CC84 to CC86
<ul style="list-style-type: none"> • for add-on terminals 	does not exist
connection method / header	
Terminals	
<ul style="list-style-type: none"> • Terminal type 	Push-in terminal
<ul style="list-style-type: none"> • Conductor cross-section, min. 	0.14 mm ² ; AWG 26
<ul style="list-style-type: none"> • Conductor cross-section, max. 	2.5 mm ² ; AWG 14
<ul style="list-style-type: none"> • Number of process terminals to I/O module 	12; Pro slot
<ul style="list-style-type: none"> • Number of terminals to AUX bus 	0
<ul style="list-style-type: none"> • Number of add-on terminals 	0
<ul style="list-style-type: none"> • Number of terminals with connection to P1 and P2 bus 	0; Pro slot
Dimensions	
Width	20 mm
Height	117 mm
Depth	35 mm
Weights	
Weight, approx.	47 g
last modified:	2/11/2021 