



Miniature circuit breaker 240 V 14kA, 1-pole, C, 3 A, D=70 mm according to UL 489

Model	
product brand name	SENTRON
product designation	Miniature circuit breakers
design of the product	Miniature circuit-breaker 5SJ4
General technical data	
number of poles	1
tripping characteristic class	C
mechanical service life (switching cycles) / typical	10 000
installation environment regarding EMC	Suitable for environment B (immunity to interference not applicable)
reference code / acc. to DIN 40719 extended according to IEC 204-2 / acc. to IEC 750	F
overvoltage category	3
degree of pollution	3
Voltage	
insulation voltage (U <sub>i</sub> ) / at AC / rated value	440 V
Supply voltage	
supply voltage / at AC / rated value	400 V
operating voltage	
<ul style="list-style-type: none"> <li>at AC / acc. to UL 489 and CSA C22.2 No. 5-02 / maximum</li> </ul>	240 V
<ul style="list-style-type: none"> <li>at DC / rated value / maximum</li> </ul>	60 V
<ul style="list-style-type: none"> <li>at DC / single channel / acc. to UL 489 and CSA C22.2 No. 5-02 / maximum</li> </ul>	60 V
<ul style="list-style-type: none"> <li>at DC / 2-channel / acc. to UL 489 and CSA C22.2 No. 5-02 / maximum</li> </ul>	125 V
Protection class	
protection class IP	IP20, with connected conductors, IP 40 in the handle range
Switching capacity	
switching capacity current	
<ul style="list-style-type: none"> <li>acc. to EN 60898 / rated value</li> </ul>	10 kA
<ul style="list-style-type: none"> <li>acc. to IEC 60947-2 / rated value</li> </ul>	15 kA
Dissipation	
power loss [W] / for rated value of the current / at AC / in hot operating state / per pole	1.8 W
Current	
operational current	
<ul style="list-style-type: none"> <li>at 30 °C / rated value</li> </ul>	3 A
<ul style="list-style-type: none"> <li>at 40 °C / rated value</li> </ul>	3 A
<ul style="list-style-type: none"> <li>at 45 °C / rated value</li> </ul>	2.9 A
<ul style="list-style-type: none"> <li>at 50 °C / rated value</li> </ul>	2.8 A

<ul style="list-style-type: none"> <li>at 55 °C / rated value</li> <li>at 60 °C / rated value</li> <li>at AC / rated value</li> </ul>	2.7 A		
	2.6 A		
	3 A		
<b>Main circuit</b>			
type of voltage supply / at AC / acc. to UL 489 and CSA C22.2 No. 5-02	240		
suitability for operation	Mechanical engineering / industry		
<b>Product details</b>			
product component / neutral conductor switching	No		
product feature / touch protection	Yes		
product component			
<ul style="list-style-type: none"> <li>tunnel terminals top</li> <li>tunnel terminals bottom</li> <li>combined terminal top</li> <li>combined terminal bottom</li> </ul>	No No Yes Yes		
product feature			
<ul style="list-style-type: none"> <li>halogen-free</li> <li>sealable</li> <li>silicon-free</li> </ul>	Yes Yes Yes		
product extension / installable / supplementary devices	Yes		
<b>Product function</b>			
product function / note	Terminal tightening torque for Cu, 60/75°C; 3.5Nm/31lb.in		
<b>Short circuit</b>			
breaking capacity short-circuit current (I <sub>cn</sub> ) / at AC / acc. to UL 1077 and CSA C22.2 No.235	14 kA		
<b>Connections</b>			
connectable conductor cross-section / finely stranded / with core end processing			
<ul style="list-style-type: none"> <li>minimum</li> <li>maximum</li> </ul>	0.75 mm <sup>2</sup> 25 mm <sup>2</sup>		
tightening torque / with screw-type terminals / maximum	3.5 N·m		
position / of power supply cord	Any		
<b>Mechanical Design</b>			
height	110 mm		
width	18 mm		
depth	70 mm		
installation depth	70 mm		
number of modular width units	1		
fastening method	on standard mounting rail		
mounting position	any		
net weight	169 g		
<b>Environmental conditions</b>			
vibration resistance	50 m/s <sup>2</sup> at 25 to 150Hz and 60m/s <sup>2</sup> at 35Hz (4sec)		
ambient temperature / during operation			
<ul style="list-style-type: none"> <li>minimum</li> <li>maximum</li> </ul>	55 °C -25 °C		
ambient temperature / during storage			
<ul style="list-style-type: none"> <li>minimum</li> <li>maximum</li> </ul>	-40 °C 75 °C		
<b>Certificates</b>			
reference code			
<ul style="list-style-type: none"> <li>acc. to DIN EN 61346-2</li> <li>acc. to IEC 81346-2</li> </ul>	F F		
<b>General Product Approval</b>		<b>Declaration of Conformity</b>	<b>Test Certificates</b>



[Miscellaneous](#)

[Special Test Certificate](#)[Miscellaneous](#)**Further information****Information- and Downloadcenter (Catalogs, Brochures,...)**<http://www.siemens.com/lowvoltage/catalogs>**Industry Mall (Online ordering system)**<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mfib=5SJ4103-7HG41>**Service&Support (Manuals, Certificates, Characteristics, FAQs,...)**<https://support.industry.siemens.com/cs/ww/en/ps/5SJ4103-7HG41>**Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)**[http://www.automation.siemens.com/bilddb/cax\\_en.aspx?mfib=5SJ4103-7HG41](http://www.automation.siemens.com/bilddb/cax_en.aspx?mfib=5SJ4103-7HG41)**CAX-Online-Generator**<http://www.siemens.com/cax>**Tender specifications**<http://www.siemens.com/specifications>

