



Figure similar

SIMATIC S7-300, Digital output SM 322, Isolated 16 DO, 120/230 V AC, 1 A, 1x 20-pole

Supply voltage	
Load voltage L1	
• Rated value (AC)	230 V; 120/230 V AC
• permissible range, lower limit (AC)	79 V
• permissible range, upper limit (AC)	264 V
Input current	
from load voltage L1 (without load), max.	2 mA
from backplane bus 5 V DC, max.	200 mA
Power loss	
Power loss, typ.	8.6 W
Digital outputs	
Number of digital outputs	16
Short-circuit protection	Yes; Fuse 8 A, 250 V; per group
• required current for fuse shutdown, min.	40 A
• Response time, max.	300 ms
Controlling a digital input	Yes
Size of motor starters according to NEMA, max.	4 NEMA compliant
Spare fuses	8 A / quick response
Switching capacity of the outputs	
• on lamp load, max.	50 W
Output voltage	
• for signal "1" (at max. current), min.	L1 (-1.5 V)
• for signal "1" (at min. current), min.	L1 (-8.5 V)
Output current	
• for signal "1" rated value	1 A
• for signal "1" permissible range for 0 to 40 °C, min.	10 mA
• for signal "1" permissible range for 0 to 40 °C, max.	1 A
• for signal "1" permissible range for 40 to 60 °C, min.	10 mA
• for signal "1" permissible range for 40 to 60 °C, max.	0.5 A
• for signal "1" minimum load current	10 mA
• for signal "1" permissible surge current, max.	20 A; with 2 half waves
• for signal "0" residual current, max.	2 mA
Parallel switching of two outputs	
• for uprating	No
• for redundant control of a load	Yes; only outputs of the same group
Switching frequency	
• with resistive load, max.	10 Hz

<ul style="list-style-type: none"> • with inductive load, max. 	0.5 Hz
<ul style="list-style-type: none"> • with inductive load (acc. to IEC 60947-5-1, AC15), max. 	0.5 Hz
<ul style="list-style-type: none"> • on lamp load, max. 	1 Hz
Total current of the outputs (per group)	
horizontal installation	
— up to 40 °C, max.	4 A
— up to 60 °C, max.	2 A
vertical installation	
— up to 40 °C, max.	2 A
Cable length	
<ul style="list-style-type: none"> • shielded, max. 	1 000 m
<ul style="list-style-type: none"> • unshielded, max. 	600 m
Interrupts/diagnostics/status information	
Diagnostics function	Yes; Fuse blown or load voltage missing
Alarms	
<ul style="list-style-type: none"> • Diagnostic alarm 	No
Diagnoses	
<ul style="list-style-type: none"> • Wire-break 	No
<ul style="list-style-type: none"> • Short-circuit 	No
<ul style="list-style-type: none"> • Fuse blown 	Yes
<ul style="list-style-type: none"> • missing load voltage 	No
Diagnostics indication LED	
<ul style="list-style-type: none"> • Rated load voltage PWR (green) 	No
<ul style="list-style-type: none"> • Fuse OK FSG (green) 	Yes; Red LED for fuse
<ul style="list-style-type: none"> • Group error SF (red) 	Yes
<ul style="list-style-type: none"> • Status indicator digital output (green) 	Yes
Potential separation	
Potential separation digital outputs	
<ul style="list-style-type: none"> • between the channels, in groups of 	8
<ul style="list-style-type: none"> • between the channels and backplane bus 	Yes; Optocoupler
Isolation	
Isolation tested with	4 000 V DC
connection method / header	
required front connector	20-pin
Dimensions	
Width	40 mm
Height	125 mm
Depth	120 mm
Weights	
Weight, approx.	275 g

last modified: 1/16/2021 