

MLFB-Ordering data

6FC5203-0AF20-0AA1



Figure similar

Client order no. :

Order no. :

Offer no. :

Remarks :

Item no. :

Consignment no. :

Project :

Rated data

Input voltage	DC 5.25 V
Power consumption, max.	0.40 W
Transmission link	3.00 m (9.84 ft)

Mechanical data

Net weight	1.3 kg (2.87 lb)
Width	483 mm (19.02 in)
Height	133 mm (5.24 in)
Depth	31 mm (1.22 in)

Degree of protection

Front side	IP54
Rear side	IP00

Mounting surface

Cutout width	450 mm (17.72 in)
Cutout height	112 mm (4.43 in)

Ambient conditions

Climate class according to EN60721-3-3 Condensation and icing excluded. Low air temperature 0 °C (32 °F).

Ambient temperature

Operation on the front	0 ... 45 °C (32 ... 113 °F)
Operation at the rear	0 ... 55 °C (32 ... 131 °F)
Transport	-40 ... 70 °C (-40 ... 158 °F)
Storage	-25 ... 55 °C (-13 ... 131 °F)

Relative humidity

Operation	5 ... 95 %
Storage	5 ... 95 %
Transport	5 ... 95 %

Approvals

Certificate of suitability	CE
----------------------------	----