



Miniature circuit breaker 240 V 14kA, 1-pole, C, 5A, D=70 mm according to UL 489, equal polarity

Model	
product brand name	SENTRON
product designation	Miniature circuit breakers
design of the product	Miniature circuit-breaker 5SJ4
General technical data	
number of poles	1
tripping characteristic class	C
mechanical service life (switching cycles) / typical	10 000
installation environment regarding EMC	Suitable for environment B (immunity to interference not applicable)
reference code / acc. to DIN 40719 extended according to IEC 204-2 / acc. to IEC 750	F
overvoltage category	3
degree of pollution	3
Voltage	
insulation voltage (U _i) / at AC / rated value	440 V
Supply voltage	
supply voltage / at AC / rated value	400 V
operating voltage	
• at AC / acc. to UL 489 and CSA C22.2 No. 5-02 / maximum	120 V
• at DC / rated value / maximum	60 V
• at DC / single channel / acc. to UL 489 and CSA C22.2 No. 5-02 / maximum	60 V
Protection class	
protection class IP	IP20, with connected conductors, IP 40 in the handle range
Switching capacity	
switching capacity current	
• acc. to EN 60898 / rated value	10 kA
• acc. to IEC 60947-2 / rated value	15 kA
Dissipation	
power loss [W] / for rated value of the current / at AC / in hot operating state / per pole	2.9 W
Current	
operational current	
• at 30 °C / rated value	5 A
• at 40 °C / rated value	5 A
• at 45 °C / rated value	4.9 A
• at 50 °C / rated value	4.8 A
• at 55 °C / rated value	4.6 A

<ul style="list-style-type: none"> at 60 °C / rated value at AC / rated value 	4.5 A 5 A	
Main circuit		
type of voltage supply / at AC / acc. to UL 489 and CSA C22.2 No. 5-02	240/120	
suitability for operation	Mechanical engineering / industry	
Product details		
product component / neutral conductor switching	No	
product feature / touch protection	Yes	
product component <ul style="list-style-type: none"> tunnel terminals top tunnel terminals bottom combined terminal top combined terminal bottom 	No No Yes Yes	
product feature <ul style="list-style-type: none"> halogen-free sealable silicon-free 	Yes Yes Yes	
product extension / installable / supplementary devices	Yes	
Product function		
product function / note	Terminal tightening torque for Cu, 60/75°C; 3.5Nm/31lb.in	
Short circuit		
breaking capacity short-circuit current (I _{cn}) / at AC / acc. to UL 1077 and CSA C22.2 No.235	14 kA	
Connections		
connectable conductor cross-section / finely stranded / with core end processing <ul style="list-style-type: none"> minimum maximum 	0.75 mm ² 25 mm ²	
tightening torque / with screw-type terminals / maximum	3.5 N·m	
position / of power supply cord	Any	
Mechanical Design		
height	90 mm	
width	18 mm	
depth	70 mm	
installation depth	70 mm	
number of modular width units	1	
fastening method	on standard mounting rail	
mounting position	any	
net weight	154 g	
Environmental conditions		
vibration resistance	50 m/s ² at 25 to 150Hz and 60m/s ² at 35Hz (4sec)	
ambient temperature / during operation <ul style="list-style-type: none"> minimum maximum 	55 °C -25 °C	
ambient temperature / during storage <ul style="list-style-type: none"> minimum maximum 	-40 °C 75 °C	
Certificates		
reference code <ul style="list-style-type: none"> acc. to DIN EN 61346-2 acc. to IEC 81346-2 	F F	
General Product Approval	Declaration of Conformity	Test Certificates



[Miscellaneous](#)

[Special Test Certificate](#)

[Miscellaneous](#)

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=5SJ4111-7HG40>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/5SJ4111-7HG40>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5SJ4111-7HG40

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>



