



SITOP UPS1100/BATTERY MODULE/24V/12AH

SITOP UPS1100 battery module with maintenance-free sealed lead batteries for SITOP DC UPS module 24 V DC 12 Ah *Ex approval no longer available*

Charging current charging voltage	
end-of-charge voltage at DC	
<ul style="list-style-type: none"> at -10 °C recommended at 0 °C recommended at 10 °C recommended at 20 °C recommended at 30 °C recommended at 40 °C recommended at 50 °C recommended 	28 V 28 V 27.8 V 27.3 V 26.8 V 26.6 V 26.3 V
Output	
Rated current value I _{out} rated	40 A
Permissible charging current, max.	3 A
Rated voltage V _{out} DC	24 V
Safety	
Short-circuit protection	Battery fuse 2x 25 A/32 V (solid-state circuitry blade-type fuse + support)
design of the overload protection	Valve control
Status display	LED green: Battery OK; LED flashing green: Error or warning; OFF: No communication
Safety	
Protection class	Class III
Degree of protection (EN 60529)	IP20
Approvals	
CE mark	Yes
UL/cUL (CSA) approval	cURus-Recognized (UL 1778, CSA C22.2 No. 107.1), File E219627
Approvals	Yes
Marine approval	ABS, DNV GL
environmental conditions	
Operating data note	For storage, mounting and operation of lead-acid batteries, the relevant DIN/VDE regulations or country-specific regulations (e.g. VDE 0510 Part 2/EN 50272-2) must be observed. You must ensure that the battery site is sufficiently ventilated. Possible sources of ignition must be at least 50 cm away.
ambient temperature	
<ul style="list-style-type: none"> during operation during transport during storage 	-15 ... +50 °C -20 ... +50 °C -20 ... +40 °C
relative temporary capacity loss at 20 °C in a month typical	3 %
Service life	

service life of energy storage	capacity falls to 80 % of original capacity (according to EUROBAT)
<ul style="list-style-type: none"> • typical note • at 20 °C typical • at 30 °C typical • at 40 °C typical • at 50 °C typical 	<p>4 y</p> <p>2 y</p> <p>1 y</p> <p>0.5 y</p>
ambient temperature during storage note	Along with the storage and operating temperature, other factors such as the duration of the storage period and the charge status during storage have a decisive influence on the possible useful life. Batteries should therefore be stored as briefly as possible, always fully charged, and within the temperature range 0 to +20 °C.
Mechanics	
Connection technology	screw-type terminals
Connection for power supply unit	1 screw terminal each for 0.5 ... 16 mm ² for + BAT and - BAT
type of electrical connection for control circuit and status message	1 screw terminal each for 0.14 ... 4 mm ²
product component included	Accessories pack with solid-state circuitry fuse 25 A
width of the enclosure	253 mm
height of the enclosure	186 mm
depth of the enclosure	110 mm
installation width	253 mm
Installation height	201 mm
required spacing	
<ul style="list-style-type: none"> • top • bottom • left • right 	<p>15 mm</p> <p>0 mm</p> <p>0 mm</p> <p>0 mm</p>
fastening method	
<ul style="list-style-type: none"> • wall mounting • standard rail mounting • S7 rail mounting 	<p>Yes</p> <p>No</p> <p>No</p>
Installation	can be screwed onto flat surface (keyhole mounting for hooking in to M4 screws)
Weight, approx.	9.8 kg
number of cells	12
Battery	12 A·h
other information	Specifications at rated input voltage and ambient temperature +25 °C (unless otherwise specified)

