



Figure similar

SIMATIC S7-300, Analog input SM 331, isolated, 2/3/4-wire, 8 AI, Resistor, Pt100/200/1000 NI100/120/200/500/1000, CU10, characteristics according to GOST 16 (internal 24) bit, 50ms, 1x 40-pole

Supply voltage	
Load voltage L+	
<ul style="list-style-type: none"> Rated value (DC) 	24 V
<ul style="list-style-type: none"> Reverse polarity protection 	Yes
Input current	
from load voltage L+ (without load), max.	240 mA
from backplane bus 5 V DC, max.	100 mA
Power loss	
Power loss, typ.	4.6 W
Analog inputs	
Number of analog inputs	8
<ul style="list-style-type: none"> For resistance measurement 	8
permissible input voltage for voltage input (destruction limit), max.	75 V; 35 V continuous, 75 V for max. 1 s (mark to space ratio 1:20)
Input ranges	
<ul style="list-style-type: none"> Voltage 	No
<ul style="list-style-type: none"> Current 	No
<ul style="list-style-type: none"> Thermocouple 	No
<ul style="list-style-type: none"> Resistance thermometer 	Yes
<ul style="list-style-type: none"> Resistance 	Yes
Input ranges (rated values), voltages	
<ul style="list-style-type: none"> 0 to +10 V 	No
<ul style="list-style-type: none"> 1 V to 5 V 	No
<ul style="list-style-type: none"> 1 V to 10 V 	No
<ul style="list-style-type: none"> -1 V to +1 V 	No
<ul style="list-style-type: none"> -10 V to +10 V 	No
<ul style="list-style-type: none"> -2.5 V to +2.5 V 	No
<ul style="list-style-type: none"> -250 mV to +250 mV 	No
<ul style="list-style-type: none"> -5 V to +5 V 	No
<ul style="list-style-type: none"> -50 mV to +50 mV 	No
<ul style="list-style-type: none"> -500 mV to +500 mV 	No
<ul style="list-style-type: none"> -80 mV to +80 mV 	No
Input ranges (rated values), currents	
<ul style="list-style-type: none"> 0 to 20 mA 	No
<ul style="list-style-type: none"> -10 mA to +10 mA 	No
<ul style="list-style-type: none"> -20 mA to +20 mA 	No
<ul style="list-style-type: none"> -3.2 mA to +3.2 mA 	No
<ul style="list-style-type: none"> 4 mA to 20 mA 	No

Input ranges (rated values), thermocouples	
• Type B	No
• Type C	No
• Type E	No
• Type J	No
• Type K	No
• Type L	No
• Type N	No
• Type R	No
• Type S	No
• Type T	No
• Type U	No
• Type TXK/TXK(L) to GOST	No
Input ranges (rated values), resistance thermometer	
• Cu 10	Yes
• Ni 100	Yes
• Ni 1000	Yes
• LG-Ni 1000	Yes
• Ni 120	Yes
• Ni 200	Yes
• Ni 500	Yes
• Pt 100	Yes
• Pt 1000	Yes
• Pt 200	Yes
• Pt 500	Yes
Input ranges (rated values), resistors	
• 0 to 150 ohms	Yes
• 0 to 300 ohms	Yes
• 0 to 600 ohms	Yes
Characteristic linearization	
• parameterizable — for resistance thermometer	Yes Pt100, Pt200, Pt500, Pt1000, Ni100, Ni120, Ni200, Ni500, Ni1000, Cu10; (standard/climate)
Cable length	
• shielded, max.	200 m
Analog value generation for the inputs	
Integration and conversion time/resolution per channel	
• Resolution with overrange (bit including sign), max.	16 bit; Two's complement
• Integration time, parameterizable	Yes
• Basic conversion time (ms)	up to 4 channels: 10 ms per module, over 5 channels: 190 ms per module, 8 channels: 80 ms
• Interference voltage suppression for interference frequency f1 in Hz	400 / 60 / 50 Hz
Encoder	
Connection of signal encoders	
• for resistance measurement with two-wire connection	Yes; without resistance correction
• for resistance measurement with three-wire connection	Yes
• for resistance measurement with four-wire connection	Yes
Errors/accuracies	
Operational error limit in overall temperature range	
• Resistance, relative to input range, (+/-)	0.1 %
• Resistance thermometer, relative to input range, (+/-)	±1 K
Basic error limit (operational limit at 25 °C)	
• Resistance, relative to input range, (+/-)	0.05 %
• Resistance thermometer, relative to input range, (+/-)	±0.5 K
Interrupts/diagnostics/status information	

Diagnostics function	Yes; Parameterizable
Alarms	
• Diagnostic alarm	Yes; Parameterizable per group
• Limit value alarm	Yes; Parameterizable
• Hardware interrupt	Yes; Parameterizable, channels 0 to 7
Diagnoses	
• Diagnostic information readable	Yes
Diagnostics indication LED	
• Group error SF (red)	Yes
Potential separation	
Potential separation analog inputs	
• between the channels	Yes
• between the channels, in groups of	2
• between the channels and backplane bus	Yes
• between the channels and the power supply of the electronics	Yes
Isolation	
Isolation tested with	500 V DC
connection method / header	
required front connector	40-pin
Dimensions	
Width	40 mm
Height	125 mm
Depth	120 mm
Weights	
Weight, approx.	272 g
last modified:	1/16/2021 